



SKYBOX | Retractable Roof Bodies BODY SPECIFICATIONS

Standard Features

- Rear and center roof sections manually slide forward converting your chip body into an open-roof vehicle for loading and hauling tall or bulky items
- Roof sections move on a stainless-steel track using maintenance-free oil-impregnated bearings to deliver years of reliable service
- Integral multi-point roof latching allows sliding roof sections to be stowed securely in both the open and closed positions
- Smooth body side panels – ideal for signage
- Rust-resistant, heavy gauge, double-panel galvanized steel side wall and tailgate construction with galvanized floor and 3-inch structural crossmembers
- Ladder box with pole pruner shelf and lockable rear door
- LED body-mounted strobe lights (set of 4)
- Undercoating on underside of floor and toolboxes to enhance durability
- Coal tar epoxy bed liner for a rugged, corrosion-resistant interior finish
- Universal White finish paint as standard (Color match paint optional)
- U.S. Patent No. D914,579 and other patents pending



Covered by ARBORTECH's



**A Single Investment
Gets You Double The
Advantage**



Manually slide roof sections forward



Slide moves on a stainless-steel track



Load or dump ready



OPTIONAL FEATURES

HELPING YOU CUSTOMIZE THE RIGHT FORESTRY BODY FOR YOU,
WE OFFER AN ARRAY OF OPTIONAL FEATURES INCLUDING:

- Ball/pintle hook combo
- Electric trailer brake control
- Amber strobe light
- 4-head LED flashing light
- LED grill-mounted strobe lights (set of 2)
- Rear underbody boxes
- Plywood / Alturna Mat storage compartment
- Back-up alarm
- Rear stirrup step and grab handle
- Front bumper cone holders
- D.O.T. 5 lb. fire extinguisher
- D.O.T. roadside triangle kit
- Toolboxes

Dimensional Data

Description:	12-ft	14-ft
Cab-to-axle (C.A.) Recommendation:	84" - 108"	102" to 120"
GVWR Recommendation:	19,500 lbs. min.	25,999 lbs. min.
Body Dimensions (L x H x W)	12' X 60" X 96"	14' X 72" X 96"
Capacity w/o cutout for toolboxes (approx.)**	7,250 lbs. / 14.50-yds ³ .	10,625 lbs. / 21.25-yds ³ .
Capacity with cutout for toolboxes (approx.)**	6,625 lbs. / 13.25-yds ³ .	10,000 lbs. / 20.00-yds ³ .

Standard Package Includes:		
LED Light Package (Stop/Tail/Turn w-4 LED Strobes)	✓	✓
Hoist Assembly with 12V Electric Pump	✓	
Hoist Assembly with Hydraulic Pump (P.T.O. required***)		✓
"L" Tool Box (48"W x 51"H x 96"D)	✓	✓
Hitch Pkg. w/T-60 Pintle (15K# - GTW)	✓	
Hitch Pkg. w/T-60 Pintle (20K# - GTW)		✓
Wheel Chock Bracket Assembly (Pair)	✓	✓
Rubber Wheel Chocks (Pair)	✓	✓

Roof Sections:		
Rear section – 42.5" overall opening	✓	✓
Center (2nd) section – 86.25" overall opening	✓	✓
Front section – 59.5" fixed (non-opening)	✓	
Front section – 84.5" fixed (non-opening)		✓

Optional Equipment:		
"I" Tool Box (24"W x 51"H x 96"D) (in lieu of "L" Box)	✓	✓
"L" Tool Box (72"W x 51"H x 96"D) (in lieu of std. "L" Box)		✓
Fixed Cone Holder (Front Bumper)	✓	✓
Underbody Tool Box (32"W x 22"H x 22"D) aft of rear axle		✓
Hitch Pkg. w/T-60 Pintle (30K# GTW) (in lieu of 10K# Pintle)		✓

** Estimated weight capacity equals cubic yards X 500 lbs.

*** P.T.O. not included with Skybox Body Package

ARBORTECH / Scott Fetzer Company

3203 W. Old Lincoln Way

Wooster, OH 44691

P: 800.255.5715 F: 330.264.7428

FOR MORE INFORMATION ON ALL OF ARBORTECH'S PRODUCTS
VISIT OUR WEBSITE:

ARBORTECHCHIPBODIES.COM

Due to constant product evaluations and improvements, specifications are subject to change without notice.

